

Compact laboratory balance KERN PCB









The standard in the laboratory

Features

- · PRE-TARE function for manual subtraction of a known container weight, useful for checking fill-levels
- · Freely programmable weighing unit, e.g. display direct in special units such as length of thread g/m, paper weight g/m², or similar
- · With the recipe function you can weigh the different ingredients of a mixture. As a check, you can also call up the total weight of all the ingredients
- · Plus/minus weighing procedures
- · Ring-shaped draught shield standard, only for models with weighing plate size A, weighing space Ø×H 90×40 mm
- · Protective working cover included with delivery

Technical data

- Backlit LCD display, digit height 15 mm
- Dimensions of weighing surface
 - A Ø 81 mm
 - **■** Ø 105 mm
 - W×D 130×130 mm
 - W×D 150×170 mm, see larger picture
- · Weighing plate material A plastic, with conductive lacquer B, C, D Stainless Steel
- Overall dimensions W×D×H 163×245×79 mm (without draught shield)
- Optional battery operation, 9 V block not included in scope of delivery, operating time up to 20 h, AUTO-OFF function to preserve the battery
- Permissible ambient temperature 5 °C/35 °C

Accessories

- Protective working cover, scope of delivery: 5 items, for models with weighing plate size
 - A KERN PCB-A02S05
 - **B** KERN PCB-A03S05
 - **III** KERN PCB-A04S05
 - KERN PCB-A05S05
- · Internal rechargeable battery pack, operating time up to 48 h without backlight, charging time approx. 8 h, KERN PCB-A01
- RS-232/Ethernet adapter for connection to an IP-based Ethernet network, KERN YKI-01
- · Balance Connection Software, KERN SCD-4.0
- · Individual header data: the free software SHM-01 can be used to print 4 header lines on the printout when using printers 911-013, YKN-01, YKB-01N, YKE-01 and YKC-01 (in combination with YKI-02)
- · Further details, plenty of further accessories and suitable printers see Accessories

STANDARD







































Model KERN	Weighing capacity [Max] g	Readability [d] g	Reproducibility	Linearity g	Weighing plate	Quality code	Option
							DAkkS Calibr. Certificate
							DAkkS
							KERN
PCB 100-3	100	0,001	0,001	± 0,003	А	AA	963-127
PCB 250-3	250	0,001	0,001	± 0,005	А	AA	963-127
PCB 350-3	350	0,001	0,002	± 0,005	Α	AA	963-127
PCB 200-2	200	0,01	0,01	± 0,02	В	AA	963-127
PCB 1000-2	1000	0,01	0,01	± 0,03	С	AA	963-127
PCB 2500-2	2500	0,01	0,01	± 0,05	С	BA	963-127
PCB 3500-2	3500	0,01	0,02	± 0,05	С	AA	963-127
PCB 1000-1	1000	0,1	0,1	± 0,2	С	AA	963-127
PCB 2000-1	2000	0,1	0,1	± 0,2	С	AA	963-127
PCB 6000-1	6000	0,1	0,1	± 0,3	D	BA	963-128
PCB 10000-1	10000	0,1	0,1	± 0,3	D	BA	963-128
PCB 6000-0	6000	1	1	± 2	D	BA	963-128

KERN BALANCES & TEST SERVICES CATALOGUE 2021



Pictograms



Internal adjusting:

Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)



Adjusting program CAL:

For quick setting up of the balance's accuracy. External adjusting weight required



Easy Touch:

Suitable for the connection, data transmission and control through PC, tablet or smartphone.



Memory:

Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.



Alibi memory:

Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard



Data interface RS-232:

To connect the balance to a printer, PC or network



RS-485 data interface:

To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible



USB data interface:

To connect the balance to a printer, PC or other peripherals



Bluetooth* data interface:

To transfer data from the balance to a printer, PC or other peripherals



WiFi data interface:

To transfer data from the balance to a printer, PC or other peripherals



Control outputs (optocoupler, digital I/O):

To connect relays, signal lamps, valves, etc.



Analogue interface:

to connect a suitable peripheral device for analogue processing of the measurements



Interface for second balance:

For direct connection of a second balance



Network interface:

For connecting the scale to an Ethernet network



KERN Communication Protocol (KCP):

It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems



GLP/ISO log:

The balance displays serial number, user ID, weight, date and time, regardless of a printer connection



GLP/ISO log:

With weight, date and time. Only with KERN printers



Piece counting:

Reference quantities selectable. Display can be switched from piece to weight



Recipe level A:

The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out



Recipe level B:

Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display



Totalising level A:

The weights of similar items can be added together and the total can be printed out



Percentage determination:

Determining the deviation in % from the target value (100 %)



Weighing units:

Can be switched to e.g. nonmetric units at the touch of a key. See balance model. Please refer to KERN's website for more details



Weighing with tolerance range:

(Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model



Hold function:

(Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value



Protection against dust and water splashes IPxx:

The type of protection is shown in the pictogram



Suspended weighing:

Load support with hook on the underside of the balance



Battery operation:

Ready for battery operation. The battery type is specified for each device



Rechargeable battery pack:

Rechargeable set



Universal mains adapter:

with universal input and optional input socket adapters for A) EU, CH, GB; B) EU, CH, GB, USA; C) EU, CH, GB, USA, AUS



Mains adapter:

230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available



Power supply:

Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request



Weighing principle: Strain gauges:

Electrical resistor on an elastic deforming body



Weighing principle: Tuning fork:

A resonating body is electromagnetically excited, causing it to oscillate



Weighing principle: Electromagnetic force compensation:

Coil inside a permanent magnet. For the most accurate weighings



Weighing principle: Single cell technology:

Advanced version of the force compensation principle with the highest level of precision



Verification possible:

The time required for verification is specified in the pictogram



DAkkS calibration possible (DKD):

The time required for DAkkS calibration is shown in days in the pictogram



Factory calibration (ISO):

The time required for Factory calibration is shown in days in the pictogram



Package shipment:

The time required for internal shipping preparations is shown in days in the pictogram



Pallet shipment:

The time required for internal shipping preparations is shown in days in the pictogram

KERN - Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAkkS calibration certificate the best pre-requisite for proper

The KERN DAkkS calibration laboratory today is one of the most modern and best-equipped DAkkS calibration laboratories for balances, test weights and force-measure-

Thanks to the high level of automation, we can carry out DAkkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

. . .

- DAkkS calibration of balances with a maximum load of up to 50 t
- DAkkS calibration of weights in the range of 1 mg 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
 Calibration of force-measuring devices
- DAkkS calibration certificates in the following languages DE, EN, FR, IT, ES, NL, PL
 Conformity evaluation and reverification of balances and test weights

Your KERN specialist dealer:

^{*}The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.